



Lacq Hardwoodoil

Lacq Hardwoodoil is a traditional recipe of blended vegetable oils to protect and maintain wooden garden furniture, ramps or teak decks annually. This hardwoodoil has a very high solids content (98%), which means that a very high coverage is achieved with the first layer. Provides long-term protection from dirt or ageing for, among others, teakwood and bankirai. This hardwoodoil is very easy to apply.

Treatment:

- Surface should be dry, dust-free and free from any surface contamination ie oil or grease. Remove any algae and moss growth and any weathered (ageing) spots from the wood using suitable preparation methods.
- Apply using a flat brush or roller. Leave for twenty minutes and remove the excess oil using a lint-free cloth. On very porous woods a second coat may be applied on the wet varnish.
- Take note: avoid building layer thickness on the surface.
- If 'chapped' areas remain visible in the wood after complete drying (approx 15 hours at 20°C), repeat the treatment.

Do not apply below 5°C and above a relative humidity of 85%.

Coverage

Approximately 6 - 9 m²/litre, dependent up on the absorbency and the surface profile.

Tip:

- + Always test in a trail area to ascertain whether you will achieve the desired finish, since variations can occur dependent upon the specific type of wood being applied on.
- + If the hardwood is severely denatured and weathered restore using a suitable proprietary hardwood restorer.
- + Hardwoodoil is only a wood impregnation oil. Consequently a surface coating cannot be built up.

Shelf life

At least 2 years from the production date if stored at a temperature between 5°C and 30°C in unopened original packaging

Safety

Ensure that any used soiled rags are disposed of responsibly preferably in an airtight container or doused with water to avoid any risk of fire.